

ANDRO 160 round


ceiling luminaire

IQ10 R 0160 R 0W 0 O 00 62 D H




ceiling recessed luminaire with opal optical; made from ASA; plain surface, no texture; installation without tools using wings; round installation housing; no passive cooling of the LED board required; no appearance of multiple shadows; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90 ; IP20; LED board replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



| | |
|---------|--|
| Project | |
| Type | |
| Notes | |
| Count | |
| Date | |

General

| |
|-------------------|
| ceiling, recessed |
| ASA |
| white |
| no texture |
| IP20 |
| interior |
| 1925 lm |

LED

| |
|---------------|
| 4000 K |
| CRI ≥ 90 |
| L80 / 50000 h |
| 2 SDCM |

Optical

| |
|------|
| opal |
|------|

Electrical

| |
|----------------------------------|
| DALI-2 dimmable |
| 16,9 Watt |
| PC1 220-240 V |
| 114 lm/W |
| no integrated emergency lighting |

Physical

| |
|-----------------------------|
| cut-out diameter 160-175 mm |
| outer diameter 190 mm |
| height 49 mm |