

# ANDRO 200 round


ceiling luminaire

IQ10 R 0200 R 0W 0 O 00 62 N H




ceiling recessed luminaire with opal optical; made from ASA; plain surface, no texture; installation without tools using wings; round installation housing; no passive cooling of the LED board required; no appearance of multiple shadows; binning initial MacAdam  $\leq 2$ SDCM; CRI  $\geq 90$ ; IP20; LED board replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



|         |  |
|---------|--|
| Project |  |
| Type    |  |
| Notes   |  |
| Count   |  |
| Date    |  |

## General

|                   |
|-------------------|
| ceiling, recessed |
| ASA               |
| white             |
| no texture        |
| IP20              |
| interior          |
| 1969 lm           |

## LED

|               |
|---------------|
| 4000 K        |
| CRI $\geq 90$ |
| L80 / 50000 h |
| 2 SDCM        |

## Optical

|      |
|------|
| opal |
|------|

## Electrical

|                                  |
|----------------------------------|
| non-dim                          |
| 16,9 Watt                        |
| PC1 220-240 V                    |
| 117 lm/W                         |
| no integrated emergency lighting |

## Physical

|                             |
|-----------------------------|
| cut-out diameter 200-215 mm |
| outer diameter 230 mm       |
| height 65 mm                |